

TSE Industries Millathane® 97 Millable Polyester Polyurethane Rubber, Hardness 62A

Category : Polymer , Thermoset , Polyester, TS , Polyurethane, TS , Thermoset Polyurethane, Elastomer, Unreinforced , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Millathane 97 is a polyether polyurethane rubber having excellent transparency, good wear properties, a high coefficient of friction and very good UV stability. This polyurethane rubber is designed for applications in shoe soling, roll coverings and all other applications where transparent, brightly colored or decorative products are desired. Formulation Millathane 97 100Stearic Acid0.25Wacker HDK-N2020Irganox 10100.25SR-231 (DEGDMA)3Luperox 2310.4All information provided by TSE Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_TSE-Industries-Millathane-97-Millable-Polyester-Polyurethane-Rubber-Hardness-62A.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	62	62	
Tensile Strength, Yield	22.59 MPa	3277 psi	
Elongation at Yield	555 %	555 %	
100% Modulus	0.00160 GPa	0.232 ksi	
200% Modulus	0.00220 GPa	0.319 ksi	
300% Modulus	0.00340 GPa	0.493 ksi	
Tear Strength	30.5 kN/m	174 pli	Die C

Optical Properties	Metric	English	Comments
Transmission, Visible	90 %	90 %	transparent; thickness not quantified

Processing Properties	Metric	English	Comments
Cure Time	8.00 min	0.133 hour	
	@Temperature 149 °C	@Temperature 300 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China