

TSE Industries Millathane® CM Millable Polyether Urethane Rubber with 45 PHR N220 Filler

Category: Polymer, Thermoset, Polyester, TS, Polyurethane, TS, Thermoset Polyurethane, Elastomer, Unreinforced, Rubber or Thermoset Elastomer (TSE)

Material Notes:

MILLATHANE CM is a sulfur and peroxide curable polyether urethane rubber. Its outstanding property is its great resistance to abrasion, which makes it of special interest for articles that are subjected to high wear in service. It has a unique combination of excellent properties, such as low temperature characteristics, and resistance to heat deterioration, ozone cracking, weathering and swelling in oils or solvents. Formulation Millathane CM 100.0N22045.0 Coumarone-Indene Resin 15.0 MBTS 4.0 MBT 1.0 Sulfur 0.75 CAYTUR 40.35 Zinc Stearate 0.50 All information provided by TSE Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_TSE-Industries-Millathane-CM-Millable-Polyether-Urethane-Rubber-with-45-PHR-N220-Filler.php

| Physical Properties | Metric | English | Comments |
|---------------------|---------------------|---------------------|----------|
| Specific Gravity | 1.22 g/cc | 1.22 g/cc | |
| MagneyVigagaity | 38 | 38 | |
| Mooney Viscosity | @Temperature 121 °C | @Temperature 250 °F | |

| Mechanical Properties | Metric | English | Comments |
|-------------------------|-------------|-----------|-----------|
| Hardness, Shore A | 77 | 77 | |
| Tensile Strength, Yield | 36.9 MPa | 5350 psi | |
| Elongation at Yield | 490 % | 490 % | |
| 100% Modulus | 0.00448 GPa | 0.650 ksi | |
| 300% Modulus | 0.0197 GPa | 2.85 ksi | |
| Tear Strength | 69.6 kN/m | 397 pli | Graves |
| Abrasion | 460 | 460 | NBS Index |
| Compression Set | 22 % | 22 % | Method B |

| Processing Properties | Metric | English | Comments |
|-----------------------|---------------------|---------------------|----------|
| Cure Time | 60.0 min | 1.00 hour | |
| | @Temperature 142 °C | @Temperature 287 °F | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com



Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China