

Taiwan Sheen Soon Sheenthane® A8510L TPU for Ink

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

Material Notes:

Thermoplastic polyurethane elastomer for inkAbrasion resistant, flexible, soft, excellent adhesion, high solubility in MEK and Anone. Used for transfer coating, screen printing, and spray applications. Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-A8510L-TPU-for-Ink.php

Physical Properties	Metric	English	Comments
Density	1.16 - 1.20 g/cc	0.0419 - 0.0434 lb/in ³	
Viscosity	3000 - 5000 cP	3000 - 5000 cP	30% solid in Anone

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	83 - 87	83 - 87	
Tensile Strength	9.81 MPa	1420 psi	
Elongation at Break	600 %	600 %	
100% Modulus	0.00687 GPa	0.996 ksi	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China