

## Taiwan Sheen Soon Sheenthane<sup>®</sup> AH-706L TPU for Hotmelt Adhesive

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

### Material Notes:

Thermoplastic polyurethane elastomer for hotmelt adhesiveHydrolysis resistance gradeExcellent bonding strength for polyester, TPU, nylon, PVC, leather, fabrics, etc. Melt flow may be customized. Used for hot melt adhesive films, seam sealing tapes, heat transfer and fabric laminations, and automotive applications.Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Taiwan-Sheen-Soon-Sheenthane-AH-706L-TPU-for-Hotmelt-Adhesive.php](http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-AH-706L-TPU-for-Hotmelt-Adhesive.php)

Physical Properties	Metric	English	Comments
Melt Flow	40 - 60 g/10 min  @Load 2.16 kg, Temperature 150 Â°C	40 - 60 g/10 min  @Load 4.76 lb, Temperature 302 Â°F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	88 - 92	88 - 92	

Thermal Properties	Metric	English	Comments
Softening Point	110 - 130 Â°C	230 - 266 Â°F	flow beginning

Descriptive Properties	Value	Comments
Tack-Free Time, min.	0.5 to 1.5	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China