

Taiwan Sheen Soon Sheenthane® AS-120L TPU for PU Adhesive

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

Material Notes:

Thermoplastic polyurethane elastomer for solvent-based polyurethane adhesive. Max. toluene solubility, MC soluble. Excellent bonding strength for polyester, TPU, nylon, PVC, leather, fabrics, etc. Used for footwear, textile laminations, furniture, spraying, and fire hose co-extrusion. Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-AS-120L-TPU-for-PU-Adhesive.php

Physical Properties	Metric	English	Comments
Viscosity	70 - 130 cP	70 - 130 cP	15% solids in MEK

Mechanical Properties	Metric	English	Comments
Peel Strength	0.0300 - 0.100 kN/m	0.171 - 0.571 pli	Initial (5 min.) PVC vs. PVC

Descriptive Properties	Value	Comments
Activation temperature (°C)	55-65	
Heat Resistance, mm	65	70°C, PVC vs PVC
Max. Toluene in Solvents (%)	50-70	
Tack Time, min	15 ~ 25	PVC vs PVC

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China