

## Taiwan Sheen Soon Sheenthane<sup>®</sup> AS-733 TPU for PU Adhesive

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

### Material Notes:

Thermoplastic polyurethane elastomer for solvent-based polyurethane adhesive. Non-yellowing, aliphatic grade. Excellent bonding strength for polyester, TPU, nylon, PVC, leather, fabrics, etc. Used for footwear, textile laminations, furniture, spraying, and fire hose co-extrusion. Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Taiwan-Sheen-Soon-Sheenthane-AS-733-TPU-for-PU-Adhesive.php](http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-AS-733-TPU-for-PU-Adhesive.php)

Physical Properties	Metric	English	Comments
Viscosity	1600 - 2000 cP	1600 - 2000 cP	15% solids in MEK

Mechanical Properties	Metric	English	Comments
Peel Strength	2.72 - 4.08 kN/m	15.5 - 23.3 pli	Initial (5 min.) PVC vs. PVC

Descriptive Properties	Value	Comments
Activation temperature (°C)	55-65	
Heat Resistance, mm	30	70°C, PVC vs PVC
Max. Toluene in Solvents (%)	30-35	
Tack Time, min	5 ~ 10	PVC vs PVC

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China