

Taiwan Sheen Soon Sheenthane® D6010E Thermoplastic Polyurethane Elastomer

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

Material Notes:

Thermoplastic polyurethane elastomer for extrusion Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-D6010E-Thermoplastic-Polyurethane-Elastomer.php

Physical Properties	Metric	English	Comments
Density	1.23 g/cc	0.0444 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	60 - 64	60 - 64	
Tensile Strength	53.9 MPa	7820 psi	
Elongation at Break	350 %	350 %	
100% Modulus	0.0245 GPa	3.55 ksi	
300% Modulus	0.0441 GPa	6.40 ksi	

Processing Properties	Metric	English	Comments
Processing Temperature	190 - 210 °C	374 - 410 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China