

Teknor Apex APEXÂ® 80457 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

Material Notes:

Notes: 105Â°C Insulation; RoHS Compliant Features: High Heat Resistance Uses: Wire and Cable Applications; Insulation Agency Ratings:

UL 1063; UL 62; UL 1581; UL 83 Forms: Pellets Wire Types: AWM; TEWInformation Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-80457-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.34 g/cc	1.34 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore C	88	88	10 seconds; ASTM D2240
Tensile Strength at Break	17.2 MPa	2500 psi	ASTM D638
Elongation at Break	300 %	300 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	105 Â°C	221 Â°F	Continuous Use; ASTM D794
Brittleness Temperature	-30.0 Â°C	-22.0 Â°F	ASTM D746
Oxygen Index	24 %	24 %	ASTM D2863

Descriptive Properties	Value	Comments
Appearance	Opaque	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China