

Teknor Apex MF 165 NT Polyvinyl Chloride, Flexible Film

Category : Polymer , Film , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMUses-Film, Medical Applications Forms-PelletsAppearance-ClearInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-MF-165-NT-Polyvinyl-Chloride-Flexible-Film.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.26 g/cc	1.26 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	87	87	15 seconds; ASTM D2240
Tensile Strength at Break	18.6 MPa	2700 psi	ASTM D412
Elongation at Break	300 %	300 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-17.0 °C	1.40 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China