

## Teknor Apex Sinvicomp DBS 8613 Polyvinyl Chloride, Rigid

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Rigid Grade

### Material Notes:

Availability: Asia Pacific Features: Good Impact Resistance Uses: Piping Forms: Powder Processing Method: Extrusion Information

Provided by Teknor Apex

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Teknor-Apex-Sinvicomp-DBS-8613-Polyvinyl-Chloride-Rigid.php](http://www.lookpolymers.com/polymer_Teknor-Apex-Sinvicomp-DBS-8613-Polyvinyl-Chloride-Rigid.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.51 g/cc	1.51 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	46.1 MPa	6680 psi	9.8 in/min; ASTM D638
Elongation at Break	130 %	130 %	9.8 in/min; ASTM D638
Izod Impact, Notched	0.491 J/cm	0.920 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	190 Å°C @Time >=1800 sec	374 Å°F @Time >=0.500 hour	Congo Red; BS 2782
Vicat Softening Point	95.0 Å°C	203 Å°F	ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China