

Teknor Apex Vidux® CV-98-PO323-G79 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Notes: 105°C Insulation Features: Conductive; Good Abrasion Resistance; Flame Retardant; Good Wear Resistance Uses: Tubing Forms:

Black Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-Vidux-CV-98-PO323-G79-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.26 g/cc	1.26 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	79	79	15 seconds; ASTM D2240
	85	85	ASTM D2240
Tensile Strength at Break	6.89 MPa	1000 psi	ASTM D638
Elongation at Break	300 %	300 %	ASTM D638
Taber Abrasion, mg/1000 Cycles	0.41	0.41	2000 Cycles, 1000 g, H-22 Wheel; ASTM D1044

Electrical Properties	Metric	English	Comments
Volume Resistivity	140 ohm-cm	140 ohm-cm	ASTM D257
Surface Resistance	120 ohm	120 ohm	ASTM D257

Descriptive Properties	Value	Comments
Appearance	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China