

Tipco Tipcolene® FPT 30 - 30% Talc Reinforced Polypropylene Homopolymer Compound

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

30% Talc Reinforced PP Homopolymer Applications: General Purpose Processing: Injection Molding Information provided by the Manufacturer, Tipco Industries Ltd., India.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Tipco-Tipcolene-FPT-30-30-Talc-Reinforced-Polypropylene-Homopolymer-Compound.php

Physical Properties	Metric	English	Comments
Density	1.12 g/cc	0.0405 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.012 cm/cm	0.012 in/in	ASTM D955
Melt Flow	8.0 g/10 min	8.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	35.0 MPa	5080 psi	ASTM D638
Elongation at Break	>= 20 %	>= 20 %	ASTM D638
Flexural Yield Strength	49.0 MPa	7110 psi	ASTM D790
Flexural Modulus	3.50 GPa	508 ksi	ASTM D790
Izod Impact, Notched (ISO)	3.00 kJ/m ²	1.43 ft-lb/in ²	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	105 °C	221 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China