

Toho Tenax Pyromex® CPX 2d 312K Non-crimped Carbon Fiber

Category: Carbon, Carbon Fiber, Other Engineering Material, Composite Fibers

Material Notes:

Pyromex® is an oxidized organic polyacrylonitrile (PAN) fiber with excellent heat and flame resistance. It also features excellent resistance to chemicals and good electrical insulation properties. In addition, unlike inorganic fibers, this yarn is highly processable for yarn spinning and weaving. Pyromex® is widely used in anti-spattering sheets for welding, fleeces or needle felts for heat protection in the auto or aerospace industries, heat protective clothing, protective covering for furnaces, heat insulators, brake or clutch discs, and high temperature carbon/carbon composite (C/C) parts. It is available as tow or staple fiber. Information provided by Toho Carbon Fibers, a wholly owned subsidiary of Toho Tenax Co., Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Toho-Tenax-Pyromex-CPX-2d-312K-Non-crimped-Carbon-Fiber.php

Physical Properties	Metric	English	Comments
Density	1.41 g/cc	0.0509 lb/in³	
Water Absorption at Saturation	7.0 %	7.0 %	Typical Moisture Content
Fiber Count	2.20 dtex	1.98 denier	Individual Filament
	686000 dtex	617000 denier	Tow Yield, Dry

Mechanical Properties	Metric	English	Comments
Elongation at Break	20 %	20 %	Dry
Tenacity	0.203 N/tex	2.30 g/denier	Dry

Descriptive Properties	Value	Comments
Finish	0.5%	
Number of Filaments	312000	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China