

Unifrax Anchor-Loc® 2200 Ceramic Fiber Modules

Category : Ceramic

Material Notes:

The Anchor-Loc® module system is a family of ceramic fiber module products designed to meet a wide range of application requirements in a variety of heat processing vessels. Ceramic fiber modules used in the Anchor-Loc systems are constructed with Durablanket® S, Durablanket HP-S, Durablanket 2600, or Fibermax® mat. Each type of Anchor-Loc ceramic fiber module can be easily fastened to interior steel shells of all types of heat processing equipment with several different attachment systems. The ceramic fiber blanket or mat is secured by two alloy tubes to a metallic module anchor. Flanges on the end of the tubes effectively lock the position of the tubes relative to the anchor at the time of installation.

Anchor-Loc Module Applications: Stress relieving furnaces, Annealing furnaces, Carbottom heat treating furnaces, Process heaters, Reheat furnaces, Furnace, kiln and boiler linings, Incineration equipment and stack linings, Soaking pit covers, Ladle covers, Ladle preheaters, Forge furnaces.

Information Provided by Unifrax I LLC

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unifrax-Anchor-Loc-2200-Ceramic-Fiber-Modules.php

Physical Properties	Metric	English	Comments
Density	0.128 g/cc	0.00463 lb/in ³	Folded
	0.160 g/cc	0.00579 lb/in ³	Durablanket-S

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1149 °C	2100 °F	Recommended Operating Temperature

Descriptive Properties	Value	Comments
Temperature Grade (°C)	1260	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China