

Unipetrol PND 33-352-94 Extra Light Fuel Oil

Category : Fluid , Solvent

Material Notes:

Extra light fuel oil is a mix of liquid hydrocarbons obtained from crude oil through distillation and other refining processes, boiling mostly within 150 to 370 °C. It may contain additives to lower its freezing point or additives to improve other characteristics. Extra light fuel oil contains colouring agent and tracers. Extra light fuel oil is designed to be used predominantly in special environmentally sensitive and protected regions requiring low-sulphur fuel, and for household heating. Information provided by Unipetrol RPA

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unipetrol-PND-33-352-94-Extra-Light-Fuel-Oil.php

Physical Properties	Metric	English	Comments
Density	0.860 g/cc	0.0311 lb/in ³	
	@Temperature 20.0 °C	@Temperature 68.0 °F	
Viscosity Measure	>= 6.0 cSt	>= 6.0 cSt	
	@Temperature 20.0 °C	@Temperature 68.0 °F	
Ash	<= 0.010 %	<= 0.010 %	
Evaporation Loss	<= 65 %	<= 65 %	
	@Temperature 250 °C	@Temperature 482 °F	
	>= 85 %	>= 85 %	
	@Temperature 350 °C	@Temperature 662 °F	

Thermal Properties	Metric	English	Comments
Melting Point	-10.0 °C	14.0 °F	
Flash Point	>= 56.0 °C	>= 133 °F	Pensky a Martens

Component Elements Properties	Metric	English	Comments
Sulfur, S	0.20 %	0.20 %	

Descriptive Properties	Value	Comments
Total Impurity Content %, max	0.05	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China