

3M 203 Masking Tape

Category: Polymer, Adhesive

Material Notes:

3M™ Masking Tape 203 is a general purpose masking tape that can be used for holding, bundling, sealing and a vast number of other jobs where a pressure- sensitive tape is needed.Information provided by 3M

Order this product through the following link: http://www.lookpolymers.com/polymer_3M-203-Masking-Tape.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------|----------|------------|
| Thickness | 119 microns | 4.70 mil | ASTM D3652 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|-------------|-----------|------------|
| Tensile Strength at Break | 29.2 MPa | 4230 psi | ASTM D3756 |
| Elongation at Break | 8.3 % | 8.3 % | ASTM D3756 |
| Peel Strength | 0.3287 kN/m | 1.875 pli | to Steel |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|---------|---------|----------------------------------|
| Maximum Service Temperature, Air | 93.0 °C | 199 °F | for up to 30 min Removes Cleanly |

| Processing Properties | Metric | English | Comments |
|-----------------------|------------|------------|----------|
| Shelf Life | 12.0 Month | 12.0 Month | |

| Descriptive Properties | Value | Comments |
|------------------------|--------|----------|
| Adhesive Type | Rubber | |
| Appearance | Tan | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China