

3M 3110 Polyethylene Protective Tapes

Category: Polymer, Adhesive

Material Notes:

3M™ Polyethylene Protective Tapes 3110 has a low-tack adhesive system to help provide temporary protection in general industrial applications for many polished metals, plastics, glass materials and for many material surfaces that are susceptible to damage caused by abrasion and marring. Since the film may contain small scratches, gels and winkles and a slight amount of haziness or visible adhesive coating pattern may be present, it is not recommended for some plastic lens, or similar applications which do not allow such visual imperfections.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-3110-Polyethylene-Protective-Tapes.php

Physical Properties	Metric	English	Comments
Thickness	76.2 microns	3.00 mil	ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	1.70 MPa	247 psi	ASTM D3759
Elongation at Break	450 %	450 %	ASTM D3759
Peel Strength	0.0219 kN/m	0.125 pli	Adhesion to Steel; ASTM D3330

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	
Appearance	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China