

3M 3350 HVAC Construction

Category : Polymer , Tape

Material Notes:

Polypropylene tape for use with flexible ducts. UL 181 B-FX Listed Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-3350-HVAC-Construction.php

Physical Properties	Metric	English	Comments
Thickness	40.6 microns	1.60 mil	Backing; ASTM D3652
	78.7 microns	3.10 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	79.9 MPa	11600 psi	ASTM D3759
Peel Strength	0.36156 kN/m	2.0625 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	110 °C	230 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China