

3M 33801 Premium Performance Aluminum Foil Tape

Category : Metal , Nonferrous Metal , Aluminum Alloy , Polymer , Tape

Material Notes:

High temperature acrylic adhesive of 425°F. UL 723 Classified Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-33801-Premium-Performance-Aluminum-Foil-Tape.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Backing; ASTM D3652
	102 microns	4.00 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	34.3 MPa	4970 psi	ASTM D3759
Peel Strength	0.438 kN/m	2.50 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	218 °C	424 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China