

3M 33803 General Purpose Aluminum Foil Tape

Category : Metal , Nonferrous Metal , Aluminum Alloy , Polymer , Tape

Material Notes:

High tack rubber adhesive. 40 lb liner. UL 723 Classified Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-33803-General-Purpose-Aluminum-Foil-Tape.php

Physical Properties	Metric	English	Comments
Thickness	45.7 microns	1.80 mil	Backing; ASTM D3652
	91.4 microns	3.60 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	28.9 MPa	4190 psi	ASTM D3759
Peel Strength	0.9861 kN/m	5.625 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	79.0 °C	174 °F	
Minimum Service Temperature, Air	-18.0 °C	-0.400 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China