

3M 3382 HVAC Construction

Category : Polymer , Tape

Material Notes:

Foil/PET laminate. Tear resistance. Roof and gutter repair tape. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-3382-HVAC-Construction.php

Physical Properties	Metric	English	Comments
Thickness	63.5 microns	2.50 mil	Backing; ASTM D3652
	114 microns	4.50 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	49.1 MPa	7120 psi	ASTM D3759
Peel Strength	0.5478 kN/m	3.125 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China