

3M 5153 PTFE Glass Cloth Tape

Category: Polymer, Tape

Material Notes:

3M™ PTFE Glass Cloth Tape 5151 is constructed using (PTFE) polytetra-fluoroethylene impregnated glass cloth and silicone adhesive. This tape is used in many applications requiring high temperature performance and high abrasion resistance. It also comes in a premium grade a liner version.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-5153-PTFE-Glass-Cloth-Tape.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------|----------|---------------------|
| Thickness | 147 microns | 5.80 mil | Backing; ASTM D3752 |
| | 203 microns | 8.00 mil | Total; ASTM D3752 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|--------------|------------|-------------------------------|
| Tensile Strength at Break | 254 MPa | 36800 psi | ASTM D3759 |
| Peel Strength | 0.47112 kN/m | 2.6875 pli | Adhesion to Steel; ASTM D3330 |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|----------|
| Maximum Service Temperature, Air | 260 °C | 500 °F | |
| Minimum Service Temperature, Air | -73.0 °C | -99.4 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------------|----------|
| Adhesive Type | Silicone | |
| Appearance | Light Brown | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel : +86 021-51131842 Mobile : +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China