

3M 7000PL Photoluminescent Film

Category: Polymer, Film

Material Notes:

3M Photoluminscent Film 7000PL is a high performance photoluminescent for film for safety and emergency exit signage. Meets and exceeds ASTM E207210, IMO A.752, OSHA 1910, 2000 IBC, DIN-67510 Part 4Rechargeable "glow in the dark" signs and markingsDimensionally stable, durable, multilayer filmExcellent chemical and stain resistanceEasily cleaned with 3M citrus Base CleanerNo radioactive materials used in manufacture of this productMay be safely disposed of in a sanitary landfill or by incinerationMay be imaged using 3M Scotchcal Screen Printing Inks 1900 and 9800 or thermal transfer methodsInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-7000PL-Photoluminescent-Film.php

Physical Properties	Metric	English	Comments
Thickness	229 - 279 microns	9.00 - 11.0 mil	film and adhesive

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	Application
	90.0 °C	194 °F	Service
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	Service
	10.0 °C	50.0 °F	Application

Descriptive Properties	Value	Comments
Appearance	Glossy appearance, light yellow green color	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China