

3M 8992L Polyester Tape

Category : Polymer , Tape

Material Notes:

3M™ Polyester Tape 8992L is a dark green polyester tape with silicone adhesive. It can be used in a large variety of high temperature applications including powdercoat masking, flashbreaker, and bag sealing applications. Additional applications include, splicing, tabbing or roll closing silicone treated liners or materials. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-8992L-Polyester-Tape.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Backing; ASTM D3752
	76.2 microns	3.00 mil	Liner; ASTM D3752
	81.3 microns	3.20 mil	Total; ASTM D3752

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	78.3 MPa	11400 psi	ASTM D3759
Elongation at Break	46 %	46 %	ASTM D3759
Peel Strength	0.482 kN/m	2.75 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 °C	399 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Silicone	
Appearance	Dark Green	
Liner	Polyester	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China