

3M 9325 Squeak Reduction Tape

Category : Polymer , Tape

Material Notes:

3M™ Squeak Reduction Tapes are a film tape for the automotive industry to help control squeaks and rattles due to vibration or wear of metal and plastic materials. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9325-Squeak-Reduction-Tape.php

Physical Properties	Metric	English	Comments
Water Absorption	0.010 %	0.010 %	
Thickness	50.8 microns	2.00 mil	Liner; ASTM D3752
	76.2 microns	3.00 mil	Backing; ASTM D3752
	127 microns	5.00 mil	Total without liner; ASTM D3752

Mechanical Properties	Metric	English	Comments
Elongation at Break	175 %	175 %	ASTM D3759
Peel Strength	0.5478 kN/m	3.125 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	107 °C	225 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China