

3M AC-770 Class B-1 Aerospace Sealant

Category: Polymer, Thermoset

Material Notes:

3M Ac-770 Class B Sealants have outstanding resistance to aviation gasoline and jet fuel, as well as resistance to chemicals and petroleum products common to the aircraft industry. 3M AC-770 Class B Sealants maintain flexibility and bond strength on most metal substrates like aluminum, titanium, stainless steel, steel, and many coatings under extremes of temperature, weathering and stress. The mixed compound is a thixotropic paste easily applied by extrusion, injection gun or spatula. They have excellent tooling properties. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-AC-770-Class-B-1-Aerospace-Sealant.php

| Physical Properties | Metric | English | Comments |
|----------------------|---------------------|---------------------|-------------------------|
| Density | 1.10 g/cc | 0.0397 lb/in³ | cured 14 days @ 50% RH |
| Volatiles | 1.5 % | 1.5 % | |
| Brookfield Viscosity | 950000 - 1.30e+6 cP | 950000 - 1.30e+6 cP | Base, RVF #7 sp @ 2 rpm |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|--|--|--|
| Hardness, Shore A | 42 - 48 | 42 - 48 | cured 14 days @ 50% RH |
| Tensile Strength at Break | 1.72 MPa | 249 psi | Standard Cure in ASTM Fuel B in ASTM D471 Reference Fuel B |
| | @Temperature 336 °C | @Temperature 637 °F | |
| | 1.83 MPa | 265 psi | |
| | @Temperature 49.0 °C, Time 173000 sec | @Temperature 120 °F, Time 48.0 hour | |
| Elongation at Break | 330 % | 330 % | 7 days @ 49°C in ASTM Fuel B 48 hrs @ 49°C |
| | 310 % | 310 % | Standard Cure in ASTM Fuel B in ASTM D471 Reference Fuel B |
| | @Time 1.21e+6 sec | @Time 336 hour | |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|------------------------|
| Maximum Service Temperature, Air | 121 °C | 250 °F | cured 14 days @ 50% RH |
| Minimum Service Temperature, Air | -54.0 °C | -65.2 °F | cured 14 days @ 50% RH |

| Processing Properties | Metric | English | Comments |
|-----------------------|---------------|------------------|----------------|
| Cure Time | 180 - 240 min | 3.00 - 4.00 hour | Tack-Free Time |



| Processing Properties | Metric 60 min | English ⁰⁰ hour | Comments |
|-----------------------|-------------------------|----------------------------|----------|
| | 9.00 Month | 9.00 Month | |
| Shelf Life | @Temperature <= 26.7 °C | @Temperature <=80.1 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|------------|-------------|
| Appearance | Brown | Accelerator |
| | Dark Brown | |
| | Off White | Base |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China