

3M Dyneon™ TF 2071USZ PTFE

Category: Polymer, Thermoplastic, Fluoropolymer, PTFE

Material Notes:

PTFE fine powder paste extrusion resin designed for high quality tubing and wire & cable insulation at reduction ratio up to 1600:1Tailored for extrusion of wire and cable insulation, tapes, tubes, liners and profiles.Includes standard grades of unmodified PTFE as well as modified grades of TFM™ PTFE.Information provided by Dyneon, A 3M Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Dyneon-TF-2071USZ-PTFE.php

| Physical Properties | Metric | English | Comments |
|---------------------|------------|---------------|----------|
| Bulk Density | 0.510 g/cc | 0.0184 lb/in³ | |

| Descriptive Properties | Value | Comments |
|------------------------|--------|----------------------|
| Extrusion Pressure | 53 MPa | reduction ratio 1600 |
| Reduction Ratio | >20 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China