

3M F-9755PC Adhesive Transfer Tapes with 420 Adhesive

Category: Polymer, Adhesive

Material Notes:

2.0 mil, 420 high tack acrylic adhesive with 4.2 mil, 58 lb polycoated kraft paper liner. Features: 2.0 mil adhesive transfer tape. 58 lb polycoated kraft paper liner. 420 Acrylic AdhesiveHigh tack adhesive. Can be applied in temperatures as low as 32 degrees FahrenheitBonds gaskets and foams. Bonds polycarbonate instrument panels. General Industrial Applications, Automotive, TransportationThis is good for adhering, joining, affixing, bonding, mounting, holding, and attaching dissimilar materials. Plastic film lamination bonding, splicing, foam laminating, Gasket and foam attachmentInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-F-9755PC-Adhesive-Transfer-Tapes-with-420-Adhesive.php

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	Release Liner
	127 microns	5.00 mil	Tape Only

Mechanical Properties	Metric	English	Comments
Peel Strength	0.60259 kN/m	3.4375 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	Long term
	323 °C	613 °F	Short term

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments	
Adhesive Type	420		
Appearance	Clear		
Liner	Moisture Resistant Tan Paper	Moisture Resistant Tan Paper	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China