

## 3M Novec™ 71DE Engineered Fluid

Category : Fluid

**Material Notes:**

3M™ Novec™ 71DE is an azeotrope containing 3M™ Novec™ 7100 and 1,2 trans-dichloroethylene. It maintains a constant liquid and vapor composition at its boiling point. It can be used in many medium-duty cleaning and degreasing applications. Feature and Benefits: Non flammable Non-conductive Low toxicity Low Global Warming Potential (GWP) Zero ozone depletion potential Low surface tension penetrates tight spaces for improved cleaning Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Novec-71DE-Engineered-Fluid.php](http://www.lookpolymers.com/polymer_3M-Novec-71DE-Engineered-Fluid.php)

Physical Properties	Metric	English	Comments
Density	1.37 g/cc	0.0495 lb/in <sup>3</sup>	Liquid
Viscosity	0.45 cP	0.45 cP	
Vapor Pressure	0.511 bar	383 torr	
Surface Tension	16.6 dynes/cm	16.6 dynes/cm	

Thermal Properties	Metric	English	Comments
Heat of Vaporization	201.0 J/g	86.45 BTU/lb	
Boiling Point	41.0 °C	106 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China