

## 3M Novec™ 72DE Engineered Fluid

Category : Fluid

**Material Notes:**

3M™ Novec™ 72DE is intended for heavy duty cleaning and degreasing applications. The high solvency and low toxicity make it an ideal replacement for ozone-depleting compounds, chlorinated solvents, and n-propyl bromide in many applications. Feature and Benefits: Non-flammable Non-conductive Low toxicity Low Global Warming Potential (GWP) Zero ozone depletion potential Low surface tension penetrates tight spaces for improved cleaning Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Novec-72DE-Engineered-Fluid.php](http://www.lookpolymers.com/polymer_3M-Novec-72DE-Engineered-Fluid.php)

Physical Properties	Metric	English	Comments
Density	1.28 g/cc	0.0462 lb/in <sup>3</sup>	Liquid
Viscosity	0.45 cP	0.45 cP	
Vapor Pressure	0.467 bar	350 torr	
Surface Tension	19 dynes/cm	19 dynes/cm	

Thermal Properties	Metric	English	Comments
Heat of Vaporization	217.7 J/g	93.65 BTU/lb	
Boiling Point	43.0 °C	109 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China