

3M Novec™ Contact Cleaner/Lubricant

Category : Fluid

Material Notes:

3M™ Novec™ Contact Cleaner/Lubricant penetrates and flushes away light oils and greases from electrical and electronic equipment. Removes fluorinated oils and grease, leaving a thin protective silicone coating. Meets MIL-PRF 29608A Class L specs. Features and Benefits: Cleans and lubricates Non-flammable Excellent plastics compatibility Non-conductive, non-corrosive Meets MIL PRF 29608A Class L Low toxicity Low Global Warming Potential Contains No HCFCs, HFCs, nPB or HAPs Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Novec-Contact-CleanerLubricant.php

| Physical Properties | Metric | English | Comments |
|---------------------|---------------|---------------|----------|
| Density | 1.37 g/cc | 0.0495 lb/in³ | |
| Surface Tension | 15.3 dynes/cm | 15.3 dynes/cm | |

| Electrical Properties | Metric | English | Comments |
|-----------------------|----------------|---------------|----------|
| Dielectric Strength | >= 0.984 kV/mm | >= 25.0 kV/in | |

| Processing Properties | Metric | English | Comments |
|-----------------------|------------|------------|----------|
| Shelf Life | 12.0 Month | 12.0 Month | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China