

## 3M OFL0109 Outdoor UL Recognized Lexan Label Products

Category : Polymer , Adhesive

### Material Notes:

3M™ Outdoor UL Recognized Lexan Label Products are durable, matte clear polycarbonate overlaminates that offer excellent moisture and abrasion resistance. These lexan labels utilize 3M™ Adhesive P1400 which is a high performance tackified acrylic designed for use in demanding environments. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-OFL0109-Outdoor-UL-Recognized-Lexan-Label-Products.php](http://www.lookpolymers.com/polymer_3M-OFL0109-Outdoor-UL-Recognized-Lexan-Label-Products.php)

Physical Properties	Metric	English	Comments
Thickness	38.1 microns	1.50 mil	Liner
	76.2 microns	3.00 mil	Facestock

Mechanical Properties	Metric	English	Comments
Peel Strength	0.386 kN/m	2.20 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	60.0 °C	140 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1400 Perm 21	
Liner	Clear Polyester Liner	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China