

## 3M Scotch® 2525 Performance Flatback Tape

Category : Polymer , Adhesive

### Material Notes:

Scotch® Performance Flatback Tape 2525 is used in holding, splicing or masking applications where high adhesion strength, high temperature capability and high backing strength are required. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Scotch-2525-Performance-Flatback-Tape.php](http://www.lookpolymers.com/polymer_3M-Scotch-2525-Performance-Flatback-Tape.php)

Physical Properties	Metric	English	Comments
Thickness	241 microns	9.50 mil	ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	35.6 MPa	5160 psi	ASTM D3756
Elongation at Break	2.0 %	2.0 %	ASTM D3756
Peel Strength	0.75598 kN/m	4.3125 pli	to Steel

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	
Appearance	Orange	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China