

3M Scotch-Seal™ 2229 Mastic Tape and Pads

Category : Polymer , Adhesive

Material Notes:

3M™ Scotch-Seal™ Mastic Tape and Pads 2229 are conformable, durable, tacky mastic coated on an easy release liner. The product is designed for quick and easy insulating, padding and sealing of objects that need to be protected from adverse environmental conditions. It is well suited for corrosion protection applicants and is resistant to UV radiation. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotch-Seal-2229-Mastic-Tape-and-Pads.php

Physical Properties	Metric	English	Comments
Water Absorption	0.070 %	0.070 %	
Thickness	3180 microns	125 mil	ASTM D1000

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	0.000 °C	32.0 °F	

Electrical Properties	Metric	English	Comments
Dielectric Constant	3.26	3.26	ASTM D150
	@Frequency 60.0 Hz	@Frequency 60.0 Hz	
Dielectric Strength	14.9 kV/mm	379 kV/in	Wet or Dry; ASTM D1000
Dissipation Factor	0.80	0.80	ASTM D150

Processing Properties	Metric	English	Comments
Shelf Life	60.0 Month	60.0 Month	

Descriptive Properties	Value	Comments
Appearance	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China