

3M Scotchkote™ 445 Epoxy Slip Deterrent System

Category : Polymer , Thermoset , Epoxy

Material Notes:

Scotchkote Epoxy Slip Deterrent System 445 has been specifically developed as a 100% solids system for use with 3M Scotchkote Granular Aggregate to provide a slip deterrent finish to high risk floor surfaces. Product Features: Combines good application characteristics with excellent abrasion resistance. Designed for application by brush or roller. Suitable for use on most floor surfaces, no primer normally required. Unaffected by most industrial chemicals. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-445-Epoxy-Slip-Deterrent-System.php

Physical Properties	Metric	English	Comments
Density	1.56 g/cc	0.0564 lb/in ³	
Solids Content	100 %	100 %	
Thickness	254 microns	10.0 mil	

Processing Properties	Metric	English	Comments
Cure Time	240 min	4.00 hour	Touch Dry
	960 min	16.0 hour	Hard Dry
	10100 min	168 hour	Full Cure

Descriptive Properties	Value	Comments
Appearance	Warning Yellow	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China