

3M Scotchlite™ IJ680CR-10 Removable Reflective Graphic Film with Comply™ Adhesive

Category: Polymer, Film

Material Notes:

6-mil flexible, enclosed lens, retoreflective films; Available in white only; Similar daytime and nighttime appearance that retains most of its reflectivity when wet; Excellent angularity; Pressure-activated adhesive for easy sliding and tacking; Removable with heat; Designed for excellent cutting and weeding with computer sign cutting equipment; Air release channels for fast and easy, bubble-free graphic installation; Unprocessed film resists fuel vapors or occasional spillsInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchlite-IJ680CR-10-Removable-Reflective-Graphic-Film-with-Comply-Adhesive.php

| Mechanical Properties | Metric | English | Comments |
|-----------------------|------------|----------|-------------------------------------|
| Peel Strength | 0.456 kN/m | 2.60 pli | Adhesion to Painted aluminum panels |
| | 0.649 kN/m | 3.70 pli | Adhesion to FRP |
| | 0.841 kN/m | 4.80 pli | Adhesion to Aluminum |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|---------|---------|---|
| Maximum Service Temperature, Air | 38.0 °C | 100 °F | flat surfaces without rivets |
| | 38.0 °C | 100 °F | flat, curved or corrugated surfaces with rivets |
| Minimum Service Temperature, Air | 4.00 °C | 39.2 °F | flat surfaces without rivets |
| | 7.00 °C | 44.6 °F | flat, curved or corrugated surfaces with rivets |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China