

## 3M XR4115 Double Coated Film Tape

Category: Polymer, Adhesive

## **Material Notes:**

3M™ X-Series Industrial Attachment Tapes offer a variety of performance characteristics and product constructions to support demanding application requirements. This product line provides a range of adhesive transfer and double-coated tapes designed for attachment of paper, corrugated, films, foils, fabric, plastics and metal. Double Coated (DC) tapes provide a backing for improved handling. Adhesive Transfer Tapes (ATT) provide the thinnest bond lines. The 3M™ X-Series Tape System is manufactured in the United States by 3MInformation provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer\_3M-XR4115-Double-Coated-Film-Tape.php

Physical Properties	Metric	English	Comments
Thickness	76.2 microns	3.00 mil	Release Liner
	152 microns	6.00 mil	Таре

Mechanical Properties	Metric	English	Comments
Peel Strength	2.049 kN/m	11.69 pli	Stainless Steel, Faceside, 180° Peel, 2 mil Al
	2.323 kN/m	13.25 pli	Stainless Steel, Backside, 180° Peel, 2 mil Al

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Short Term
	66.0 °C	151 °F	Long Term

Processing Properties	Metric	English	Comments
Shelf Life	18.0 Month	18.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	High Density Polyethylene	
Adhesive Type	Synthetic Rubber	
Liner	White Densified Kraft Liner with Red Print	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China