

A. Schulman POLYFLAM™ RPP 1221 Low-Blooming, General Purpose Copolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer

Material Notes:

Description Polyflam® RPP 1221 is a low-blooming general purpose copolymer polypropylene flame retardant material with a UL-V2 flammability rating and 115°C temperature index at 0.030 in. Information provided by A. Schulman.

Order this product through the following link:

http://www.lookpolymers.com/polymer_A-Schulman-POLYFLAM-RPP-1221-Low-Blooming-General-Purpose-Copolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.950 g/cc	0.950 g/cc	ASTM D792
Melt Flow	20 g/10 min	20 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	22.0 MPa	3190 psi	ASTM D638
Elongation at Break	100 %	100 %	ASTM D638
Flexural Modulus	0.990 GPa	144 ksi	ASTM D790
Izod Impact, Notched	1.80 J/cm	3.37 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	80.0 °C	176 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	50.0 °C	122 °F	ASTM D648
UL RTI, Electrical	115 °C	239 °F	0.030 in; UL 94
Flammability, UL94	V-2	V-2	
	@Thickness 1.57 mm	@Thickness 0.0618 in	
	V-2	V-2	
	@Thickness 3.05 mm	@Thickness 0.120 in	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China