

A. Schulman PP 3491 Polypropylene Homopolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Molded

Material Notes:

Description Polypropylene PP 3491 is a low water carry over homopolymer polypropylene, designed for high speed extrusion. Information provided by A. Schulman.

Order this product through the following link:

http://www.lookpolymers.com/polymer_A-Schulman-PP-3491-Polypropylene-Homopolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.905 g/cc	0.905 g/cc	ASTM D792
Melt Flow	4.0 g/10 min @Load 2.16 kg, Temperature 230 °C	4.0 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Elongation at Break	40 %	40 %	ASTM D638
Tenacity	0.441 N/tex	5.00 g/denier	at break; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	163 °C	325 °F	by DSC

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China