

ATI Allvac® Nickelvacc® C-276 UNS N10276 Nickel Superalloy

Category : Metal , Nonferrous Metal , Nickel Alloy , Superalloy

Material Notes:

Uses: Pressure vessels, pumps, valves, HX tubing and piping for the CPI and HPI. Trays, flanges, fasteners, wire, screens. Property values are for samples in the metallurgical condition: 2050°F anneal. Information provided by Allvac, An Allegheny Teledyne Company.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ATI-Allvac-Nickelvacc-C-276-UNS-N10276-Nickel-Superalloy.php

Physical Properties	Metric	English	Comments
Density	8.94 g/cc	0.323 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell B	80	80	
Tensile Strength, Ultimate	793 MPa	115000 psi	
Tensile Strength, Yield	310 MPa @Strain 0.200 %	45000 psi @Strain 0.200 %	
Elongation at Break	65 %	65 %	
Reduction of Area	75 %	75 %	

Component Elements Properties	Metric	English	Comments
Carbon, C	0.010 %	0.010 %	
Chromium, Cr	15.5 %	15.5 %	
Cobalt, Co	0.50 %	0.50 %	
Iron, Fe	5.0 %	5.0 %	
Molybdenum, Mo	16 %	16 %	
Nickel, Ni	59 %	59 %	as balance
Tungsten, W	3.5 %	3.5 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China