

Advanced Polymer Alloys DuraGrip™ DGR 6040 NCEHT Thermoplastic Elastomer (TPE)

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Olefinic Elastomer (TPO)

Material Notes:

DuraGrip® DGR 6040NCEHT is a general purpose Thermoplastic Elastomer (TPE) designed to process easily in injection molding and extrusion. It features excellent soft touch feel with improved surface tack that produces superior grip qualities. DGR 6040NCEHT will bond to olefinics, and is easily colored. DuraGrip® is not hygroscopic and under normal conditions does not require drying. Information provided by Advanced Polymer Alloys

Order this product through the following link:

http://www.lookpolymers.com/polymer_Advanced-Polymer-Alloys-DuraGrip-DGR-6040-NCEHT-Thermoplastic-Elastomer-TPE.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.940 g/cc	0.940 g/cc	ASTM D471; ISO 2781
Viscosity	102000 cP @Shear Rate 300 1/s, Temperature 190 °C	102000 cP @Shear Rate 300 1/s, Temperature 374 °F	ASTM D3835

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	38	38	Time of 5 seconds; ASTM D2240; ISO 48
Tensile Strength, Ultimate	2.69 MPa	390 psi	ASTM D412; ISO 37
Elongation at Break	500 %	500 %	ASTM D412; ISO 37
100% Modulus	0.00138 GPa	0.200 ksi	ASTM D412; ISO 37

Processing Properties	Metric	English	Comments
Processing Temperature	216 °C	420 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China