

Anderman Ceramics EM60P Sillimanite

Category : Ceramic , Oxide , Aluminum Oxide , Silicon Oxide

Material Notes:

Porous synthetic mullite with high thermal shock. Available as tube up to 10 ft (3 m) long with diameters 0.6" to 2.4". Information provided by Anderman Ceramics.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Anderman-Ceramics-EM60P-Sillimanite.php

Physical Properties	Metric	English	Comments
Density	2.30 g/cc	0.0831 lb/in ³	
Open Porosity	22 %	22 %	

Mechanical Properties	Metric	English	Comments
Flexural Strength	37.2 MPa	5400 psi	

Thermal Properties	Metric	English	Comments
CTE, linear	6.50 µm/m-°C	3.61 µin/in-°F	
	@Temperature 20.0 - 1000 °C	@Temperature 68.0 - 1830 °F	
Thermal Conductivity	1.50 W/m-K	10.4 BTU-in/hr-ft ² -°F	
	@Temperature 20.0 - 100 °C	@Temperature 68.0 - 212 °F	
Maximum Service Temperature, Air	1400 °C	2550 °F	

Component Elements Properties	Metric	English	Comments
Al2O3	60 %	60 %	
CaO	0.19 %	0.19 %	
Fe2O3	0.73 %	0.73 %	
SiO2	39 %	39 %	
TiO2	0.36 %	0.36 %	

Electrical Properties	Metric	English	Comments
Electrical Resistivity	1.00e+6 ohm-cm	1.00e+6 ohm-cm	
	@Temperature 600 °C	@Temperature 1110 °F	

Descriptive Properties	Value	Comments
Thermal Shock Resistance	Good	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China