

## **Aremco Ceramabind™ 643-1 High Temperature Inorganic Binder**

Category: Ceramic

## **Material Notes:**

A basic solution compatible with most ceramic and metal powders. Excellent binder for producing high temperature protective coatings and refractory and chemically resistant adhesives and patching materials. Fully cures at low temperatures and sets up in thick cross-sections when properly formulated.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Aremco-Ceramabind-643-1-High-Temperature-Inorganic-Binder.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.26 g/cc	1.26 g/cc	
Solids Content	30 %	30 %	by weight
pH	11	11	
Viscosity	60 cP	60 cP	
Storage Temperature	7.22 - 35.0 °C	45.0 - 95.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1650 °C	3000 °F	

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China