

Aremco Pyro-Tape™ 682-PM High Temperature Tape Tri-layer silicone rubber/aluminum foil/ fiberglass with silicone adhesive

Category : Polymer , Adhesive , Tape

Material Notes:

Applications Plasma Spray Masking Features Multi-ply construction replaces single-ply tapes permitting significant reduction in masking time. Shadow mask tape for HVOF (high velocity oxy- fuel) spraying.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Pyro-Tape-682-PM-High-Temperature-Tape-Tri-layer-silicone-rubberaluminum-foil-fiberglass-with-silicone-adhesive.php

Physical Properties	Metric	English	Comments
Thickness	483 microns	19.0 mil	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	
Minimum Service Temperature, Air	-73.0 °C	-99.4 °F	

Descriptive Properties	Value	Comments
Adhesion	40 oz/in	
Tape Tensile Strength	130 lbs/in	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China