

## **Aremco Quartz-Coat™ 845 High Temperature Ceramic-Inorganic Coating**

Category: Ceramic, Other Engineering Material, Ceramic/Metallic Coating

## **Material Notes:**

Single part, waterborne, silicon-filled, phosphate-bonded, brown-black coating for glass and quartz to 2000 °F (1093 °C). Primarily used for marking ceramic parts and coating automotive headlamps, stadium lighting and quartz vessels for the semiconductor industry.

Standard viscosity is 200–400 cP; a higher viscosity coating, 845-HV, in the range of 500–800 cP is available upon request.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Aremco-Quartz-Coat-845-High-Temperature-Ceramic-Inorganic-Coating.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.44 g/cc	1.44 g/cc	
Solids Content	22.9 %	22.9 %	by volume
	50.1 %	50.1 %	by weight
Volatile Organic Compounds (VOC) Content	0.00 g/l	0.00 g/l	
Viscosity	200 - 400 cP	200 - 400 cP	
Thickness	25.4 microns	1.00 mil	recommended dry film thickness
	82.3 microns	3.24 mil	estimated wet film thickness
Storage Temperature	12.8 - 29.4 °C	55.0 - 85.0 °F	

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	1090 °C	2000 °F	Continuous	

Processing Properties	Metric	English	Comments	
Processing Temperature	10.0 - 32.2 °C	50.0 - 90.0 °F	Application Temperature	
Cure Time	5.00 min	0.0833 hour	Step 2	
	@Temperature 482 °C	@Temperature 900 °F	Step 2	
	10.0 min	0.167 hour	Step 1, preceeded by >10 min. air set	
	@Temperature 93.3 °C	@Temperature 200 °F	Step 1, preveeded by >10 min. an Set	
Shelf Life	6.00 Month	6.00 Month		

Descriptive Properties	Value	Comments
Color	Brown-Black	Cured



Descriptive Properties  Descriptive Properties	Value Value	comments
Thinner	845-T	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China