

Arkema Group KYNAR FLEX® 2850 PC Polyvinylidene Fluoride Spray Coating Powder

Category : Polymer , Thermoplastic , Fluoropolymer , PVDF , Polyvinylidene fluoride (PVDF), Molded/Extruded

Material Notes:

Electrostatic spray Information provided by Arkema Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-KYNAR-FLEX-2850-PC-Polyvinylidene-Fluoride-Spray-Coating-Powder.php

Physical Properties	Metric	English	Comments
Viscosity	500000 - 800000 cP	500000 - 800000 cP	Melt Viscosity; ASTM D3835
	@Shear Rate 100 1/s, Temperature 232 °C	@Shear Rate 100 1/s, Temperature 450 °F	
Melt Flow	8.0 - 25 g/10 min	8.0 - 25 g/10 min	ASTM D1238
	@Load 12.5 kg, Temperature 232 °C	@Load 27.6 lb, Temperature 450 °F	

Thermal Properties	Metric	English	Comments
Melting Point	155 - 160 °C	311 - 320 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China