

## Arkema Group Lacovyl® GB 1350 PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Transparent

## **Material Notes:**

LACOVYL GB 1350 is a vinyl chloride homopolymer produced by mass polymerization process. CHARACTERISTICS Viscosity index (ISO 1628-2):125 ml/g, (K value:70). Apparent density (ISO 60):0.55 g/ml. high rate of plasticizer absorption. high molecular weight giving articles with good mechanical properties. very good transparency. RECOMMENDED APPLICATIONS standard and transparent soling. premolded soling. EXAMPLES OF APPLICATIONS, PVC-P: NAKAN FSS 703 R NAKAN FSS 601 R ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Arkema-Group-Lacovyl-GB-1350-PVC.php

Physical Properties	Metric	English	Comments
Apparent Bulk Density	0.540 g/cc	0.0195 lb/in³	
Viscosity Test	125 cm³/g	125 cm³/g	Viscosity Number

Optical Properties	Metric	English	Comments
Transmission, Visible	80 %	80 %	Mfr. reports 'Transparent' but doesn't quantify.

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China