

## Arkema Group Lacovyl® PB 1303 PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Molded

## **Material Notes:**

LACOVYL PB 1303 is a vinyl chloride homopolymer manufactured by microsuspension polymerization process for the preparation of plastisols. It is specially designed for compact articles with low plasticizer content particularly in automotive industry, thanks to its low fogging.\* MAIN CHARACTERISTICS Viscosity index (ISO 1628-2):125 ml/g,(K value:70). \* APPLICATIONSLACOVYL PB 1303 is recommended for the following applications where low fogging is needed: compact coating for coated fabrics coating by mechanical or chemical foam techniques rotomolding (automotive industry, etc...) dip molding. ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Arkema-Group-Lacovyl-PB-1303-PVC.php

Physical Properties	Metric	English	Comments
Viscosity Test	125 cm³/g	125 cm³/g	Viscosity Number

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China