

Arkema Group OREVAC® 18910 Maleic Anhydride Modified Copolymer

Category : Polymer , Adhesive , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene , SMA Polymer

Material Notes:

OREVAC® 18910 is anhydride modified copolymer based on styrenic and ethylenic copolymers. It is available in pellet form for use in conventional extrusion and coextrusion equipment designed to process polyolefin resins. OREVAC® 18910 is typically used as adhesive to bond PS, PE, EVOH and PA in coextruded multilayer structures like films or sheets. Information provided by Arkema Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-OREVAC-18910-Maleic-Anhydride-Modified-Copolymer.php

Physical Properties	Metric	English	Comments
Density	0.950 g/cc	0.0343 lb/in³	ISO 1183
	@Temperature 23.0 °C	@Temperature 73.4 °F	
Melt Index of Compound	1.0 g/10 min	1.0 g/10 min	ISO 1133
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	

Thermal Properties	Metric	English	Comments
Melting Point	117 °C	243 °F	DSC
Vicat Softening Point	77.0 °C	171 °F	ISO 306

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China