

Arkema Group OREVAC® C306 Maleic Anhydride Modified Linear Low Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene , LLDPE

Material Notes:

OREVAC C306 is anhydride modified LLDPE. It is available in pellet form for use in conventional extrusion and coextrusion equipment designed to process polyethylene (PE) resins. It has been designed to be used pure or blended with PE. OREVAC C306 provides outstanding adhesion to PE, PA, EVOH. It is typically used to bond PE and EVOH or PA in flexible packaging. Information provided by Arkema Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-OREVAC-C306-Maleic-Anhydride-Modified-Linear-Low-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.908 g/cc	0.0328 lb/in ³	ISO 1183
	@Temperature 23.0 °C	@Temperature 73.4 °F	
Melt Index of Compound	1.0 - 1.5 g/10 min	1.0 - 1.5 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	

Thermal Properties	Metric	English	Comments
Melting Point	120 °C	248 °F	DSC

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China